

TECHNICAL DATA SHEET

JOKISCH MONOS ATOS M3S (Jokisch Ultra A 707)

Machine cutting oil, suitable for all types of metal working.

High corrosion protection - high cutting speeds – low abrasion

APPLICATION

Particularly suitable for severe to severest machining operations at medium speed in turning, milling and gear cutting machines. Not suitable for non-ferrous metals.

CHARACTERISTICS

It is a special combination of low-aromatic mineral oil and natural oils, which make it possible to pump this oil without thickening it.

- High cutting speeds
- Low tool wear
- Very good and clean surfaces
- High corrosion protection
- Highest precision
- Liquid residuals
- Easily degreasable by alkaline or cold cleaners

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH MONOS ATOS M3S
Kin. viscosity at 20°C	mm ² /s	ASTM D 7042	34
Density at 20°C	g/cm ³	EN ISO 12185	0,94
Flash point	°C	DIN EN 57	>180

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this

STORAGE

Storage temperature: 5 – 40°C
Storage time: 36 months

Jokisch GmbH
Fabrik für Schmier- und Kühlmittelspezialitäten

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokisch-fluids.de | www.jokisch-fluids.de

