

TECHNICAL DATA SHEET

JOKISCH MONOS PRIX F3G

Fluid grease for use in central lubrication systems.

APPLICATION

Grease for use in centralized lubrication systems for slideways on machine tools and pneumatic tools.

CHARACTERISTICS

The grease is based on a blend of highly refined and synthetic base oils, extreme pressure additives and other specially selected additives for excellent protection in a variety of applications.

- Good pumpability
- High water resistance
- Very good high-pressure properties

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH MONOS PRIX F3G
NLGI consistency			00/000
Thickener			Lithium-Calcium
Base oil type			Semi synthetic
Kin. viscosity at 40°C	cSt	IP 71 / ASTM D445	45
Kin. viscosity at 100°C	cSt	IP 71 / ASTM D445	7
Cone penetration, worked at 25°C	0,1mm	IP 50 / ASTM D445	440
Pumpability in long pipe			Very good

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this.

STORAGE

Storage temperature: 5 – 40°C
Storage time: 36 months

Jokisch GmbH
Fabrik für Schmier- und Kühlmittelspezialitäten

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokisch-fluids.de | www.jokisch-fluids.de

