

TECHNICAL DATA SHEET

JOKISCH MONOS VENO (Jokisch High Speed Superfine Spindle Oil)

Very fine filtrated HLP-hydraulic oil (DIN 51 524/T2).
Purity class according to ISO 4406 (15/13/10).

APPLICATION

Due to their high degree of purity, these hydraulic oils are used in particular for the lubrication of bearings in engine and high-frequency spindles.

CHARACTERISTICS

The products correspond to the purity class according to ISO standard on the level 15/13/10. They have high thermal stability, wear and corrosion protection additives, as well as excellent deterging and dispersing properties.

- High thermal stability
- Additives for increasing aging resistance
- Dispersing properties
- Low foaming tendency
- High EP-characteristics

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	032	046	068
Viscosity classes			32	46	68
Flash point	°C	DIN 51755	>190	>190	220
Setting point	°C		-20	-20	-20
Viscosity index		DIN EN ISO 12185	114	104	102
Density at 20°C	g/cm ³	DIN 51757	0,871	0,873	0,885
Viscosity at 40°C	mm ² /s	DIN 51562-1	30-35	44-49	65-73
Viscosity at 100°C	mm ² /s	DIN 51562-1	5,6	7,2	9,1

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this

STORAGE

Storage temperature: 5 – 40°C
Storage time: 36 months

Jokisch GmbH
Fabrik für Schmier- und Kühlmittelspezialitäten

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokisch-fluids.de | www.jokisch-fluids.de

