

TECHNICAL DATA SHEET

JOKISCH MONOS PRIX F2S

Multi-purpose grease of medium consistency class.

For general industrial grease lubrication, ideal for central lubrication systems at normal operating temperatures.

APPLICATION

Based on a proven lithium hydroxystearate thickener and oxidation, Wear protection as well as corrosion protection additives. Significant advantages over conventional lithium greases, especially at high temperatures or in the presence of water.

Main application areas:

- Rolling and plain bearings
- Bearings in electric motors
- Lifetime lubrication
- Water pump bearings

CHARACTERISTICS

- Reliable temperature stability up to +130°C, resulting in a longer service life of the bearings.
- Good oxidation protection and mechanical stability reduces the formation of aging products. The high shear stability of the thickener reduces the likelihood of leakage.
- Good anti-corrosive properties even in unfavorable environments.
- Does not cause consistency changes even during prolonged storage.

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH MONOS PRIX F2S
NLGI consistency			2
Thickener			Lithium- Hydroxystearat
Base oil type			Mineral oil
Kin. viscosity at 40°C	cSt	IP 71 / ASTM D445	100
Kin. viscosity at 100°C	cSt	IP 71 / ASTM D445	11
Cone penetration, worked	0.1mm	IP 50 / ASTM D217	265-295
Dropping point	°C	IP 396	180

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this

STORAGE

Storage temperature: 5 – 40°C
Storage time: 36 months

Jokisch GmbH
Fabrik für Schmier- und Kühlmittelspezialitäten

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokisch-fluids.de | www.jokisch-fluids.de

