JOKISCH MONOS PRIX F2G

Multifunction grease for various industrial application.

High strained roller bearings, which work under difficult conditions, including shock load, in damp locations.

APPLICATION

Multi-purpose grease with EP properties for high loads, on the basis of a lithium-hydroxystearate thickener and with proven additives for reliable performance.
It is ideal for lubricating rolling elements and bearings and it is very well transportable in central lubrication systems.

CHARACTERISTICS

- Outstanding load carrying capacity
- Improved mechanical stability
- Resistant to water wash off
- Oxidation stability
- Good corrosion protection properties

Suitable for the application temperature range from -20°C to + 130°C.
Care must be taken to ensure that elastomers are compatible with mineral oil (hydrocarbons). Rubber and rubber components in brake systems designed for non-mineral hydraulic fluids (e.g., polyglycol based) may be incompatible.

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH **MONOS PRIX F2G**
NLGI consistency			2
Thickener			Lithium
Base oil type			Mineral oil
Kin. viscosity at 40°C	cSt	IP 71 / ASTM D445	220
Kin. viscosity at 100°C	cSt	IP 71 / ASTM D445	19
Cone penetration,worked	0.1mm	IP 50 / ASTM D217	265-295
Dropping point	°C	IP 396	180

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this

STORAGE

Storage temperature: 5 – 40°C
Storage time: 36 months

Date: 03.04.2025

JOKOBA Technologies GmbH

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokoba.de | www.jokisch-fluids.de

jokisch® Made in Germany