

TECHNICAL DATA SHEET

JOKISCH MIGMA TANO DGY (Jokisch Compact V)

Designed for medium machining on a variety of materials.

Free of secondary amines - free of formaldehyde
Properties: stable in hard water, pressure stable

APPLICATION

Universally applicable water soluble cooling lubricant, excellent suited for general processing. Universal use due to the mineral oil content, long term stability against bacteria, also suited for internally cooled tools and high pump pressures.

CHARACTERISTICS

Formulated with low aromatic, highly refined base oils. Special emulsifiers ensure an excellent performance spectrum and high corrosion protection even at low concentrations. Particularly selected AW additives allow machining with high cutting speeds.

PROPOSED CONCENTRATION

Light machining	5%
Severe machining	7%
Severest machining	10%

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH MIGMA TANO DGY
Kin. viscosity at 20° C	mm ² /s	ASTM D 7042	180
Density at 20° C	g/cm ³	DIN EN ISO 12185	0,99
pH-value at 20° C	-	DIN 51369	9,5
Corrosion protection note 0	-	DIN 51360	5% = 0
Refractometerindex	-	-	1,7
Mineral oil content	%	-	22%

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this.

STORAGE

Storage temperature:	5 – 40° C
Storage time:	12 months

ORDER NUMBER / DELIVERY SIZE

70006IND	10 litre canister
70009IND	25 litre canister
70013IND	60 litre drum
70014IND	209 litre drum

Jokisch GmbH
Fabrik für Schmier- und Kühlmittelspezialitäten

Industriestraße 5-10 | 33813 Oerlinghausen
T + 49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokisch-fluids.de | www.jokisch-fluids.de

