

TECHNICAL DATA SHEET

JOKISCH FOTIA ALEA 1.2

Environmentally friendly, hydrated anti spatter fluid for MIG and MAG welding.

Not-flammable – silicone free - chlorinated hydrocarbon free - without solvents

APPLICATION

Ready-to-use active welding substance, can be used for most common industrial welding process. Prevents the adherence of welding spatter to the workpiece surface. Can be applied with hand sprayers, air spray cans or spraying unit. Spray the work surface slightly, apply only thin spray film.

CHARACTERISTICS

- For arc welding with electrodes, easy removal of the slag, even with V-seams
- Easy cleaning of welding seams
- Also prevents the welding spatter from burning in the burner heads during inert gas welding and contact welding.
- When used correctly no complications with further processing of priming, painting, galvanizing etc
- It is completely non flammable and can therefore be applied without risk in the workplace
- Product is exempted from the specific labelling requirements of hazardous products according to ordinance on hazardous substances
- Approval for Trumpf Trulaser Tube 3000/5000/7000
- If you have any questions please contact your contact person at Trumpf or us directly

PROPOSED CONCENTRATION

Ready for use in the mixing ratio 1:1
(50% of Jokisch Fotia Alea, and 50% water)
Immediately usable.

without Jokisch **Fotia Alea 1.1**



STORAGE

Storage temperature: 5 – 40°C
Storage time: 12 months

with Jokisch **Fotia Alea 1.1**



Content:

Article number 10600504: 5 Liter

Article number 10600506: 10 Liter

Article number 10600509: 25 Liter

Jokisch GmbH
Fabrik für Schmier- und Kühlmittelspezialitäten

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokisch-fluids.de | www.jokisch-fluids.de

