JOKISCH MIGMA TANO DPR MP

Designed for severe to severest machining for a variety of materials.

Free of secondary amines - free of formaldehyde – Free of boric acid
Properties: stable in hard water, pressure stable

APPLICATION

Universally applicable water soluble cooling lubricant, excellent suited for severe to severest processing. Of particular note here is the problem-free machining of aluminum and the demanding machining of high-alloy steels and titanium.

CHARACTERISTICS

Formulated with low aromatic, highly refined base oils, ester and polymere. Special emulsifiers ensure an excellent performance spectrum and high corrosion protection even at low concentrations. Particularly selected AW additives allow machining with high cutting speeds. Long term stability against bacteria, also suited for internally cooled tools and high pump pressures.

PROPOSED CONCENTRATION

Light machining	5%
Severe machining	7%
Severest machining	10%

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH **MIGMA TANO DPR MP**
Kin. viscosity at 20°C	mm²/s	ASTM D 7042	110
Density at 20°C	g/cm³	DIN EN ISO 12185	0,99
pH-value at 5%	-	DIN 51369	9,4
Corrosion protection note 0	-	DIN 51360	5% = 0
Refractometerindex	-	-	1,7
Mineral oil content	%	-	20 % + Polymere and Ester

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this.

STORAGE

Storage temperature:	5 – 40°C
Storage time:	12 months

Date: 12.09.2025

JOKOBA Technologies GmbH

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokoba.de | www.jokisch-fluids.de

jokisch® Made in Germany