SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Jokisch Migma Tano DSR

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	JOKOBA Technologies GmbH Germany
Street:	Industriestraße 5-10
Place:	D-33813 Oerlinghausen
Telephone:	+49(0)5202/9734-0
E-mail:	info@jokoba.de
Contact person:	Regulatory affairs
E-mail:	MSDS@jokoba.de
Internet:	www.jokisch-fluids.de

1.4. Emergency telephone number:

Emergency telephone number (24h) +1 872 5888271 (JRR) (en)

Further Information

Reserved for industrial and professional use.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard statements

EUH208	Contains 2-n-butyl-benzo[d]isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

2.3. Other hazards

Avoid release to the environment.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			15 - < 20 %
	265-159-2		01-2119480132-48	
	Asp. Tox. 1; H304			
105-59-9	2,2'-(methylimino)diethanol; N-methyldiethanolamine			5 - < 10 %
	203-312-7		01-2119488970-24	
	Carc. 2, Eye Irrit. 2; H351 H319			
68608-26-4	Sulfonic acids, petroleum, sodium salts			2.5 - < 5 %
	271-781-5		01-2119527859-22	
	Eye Irrit. 2; H319			
4299-07-4	2-n-butyl-benzo[d]isothiazol-3-one			0.1 - < 1 %
	420-590-7			
	Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H314 H318 H317 H400 H410			
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			< 0.036 %
	220-120-9	613-088-00-6		
	Acute Tox. 2, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H302 H315 H318 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-56-9	265-159-2	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	15 - < 20 %
	oral: LD50 = 5000 mg/kg		
105-59-9	203-312-7	2,2'-(methylimino)diethanol; N-methyldiethanolamine	5 - < 10 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4680 mg/kg		
68608-26-4	271-781-5	Sulfonic acids, petroleum, sodium salts	2.5 - < 5 %
	dermal: LD50 = > 5001 mg/kg; oral: LD50 = > 5001 mg/kg		
4299-07-4	420-590-7	2-n-butyl-benzo[d]isothiazol-3-one	0.1 - < 1 %
	oral: LD50 = 4267-4732 mg/kg		
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	< 0.036 %
	inhalation: ATE 0,21 mg/l (dusts or mists); oral: ATE 450 mg/kg Skin Sens. 1A; H317: >= 0,036 - 100 Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1		

Further Information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Seek medical attention if problems persist. No administration in cases of unconsiousness or cramps.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Call a doctor if you feel unwell.

After contact with skin

Remove contaminated, saturated clothing immediately. Wash with plenty of water/soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Dry extinguishing powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:
Nitrogen oxides (NOx).
Carbon monoxide
Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

See protective measures under point 7 and 8.
High slip hazard because of leaking or spilled product. Do not breathe mist/vapours/spray. Provide adequate ventilation.

For non-emergency personnel

Take off immediately all contaminated clothing and wash it before reuse.

For emergency responders

The danger areas must be delimited and identified using relevant warning and safety signs. Move victim out of danger zone.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Clean contaminated articles and floor according to the environmental legislation. Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas.
When using do not eat, drink or smoke.

Further information on handling

When using do not eat, drink or smoke.
High slip hazard because of leaking or spilled product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.
Recommended storage temperature: 5-40 °C
Maximum period of storage (time): 1 year

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
111-42-2	Diethanolamine (Inhalable Fraction and Vapour)	0.2	1		TWA (8 h)	
1310-73-2	Sodium hydroxide	-	2		STEL (15 min)	
102-71-6	Triethanolamine	-	5		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m³
Worker DNEL, long-term		inhalation	local	5,58 mg/m³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m³
105-59-9	2,2'-(methylimino)diethanol; N-methyldiethanolamine			
Worker DNEL, long-term		inhalation	systemic	7,9 mg/m³
Worker DNEL, long-term		dermal	systemic	5,6 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0,05 mg/cm²
Consumer DNEL, long-term		inhalation	systemic	0,4 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,67 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,03 mg/cm²
Consumer DNEL, long-term		oral	systemic	0,13 mg/kg bw/day
102-71-6	Triethanolamin			
Worker DNEL, long-term		inhalation	local	1 mg/m³
Worker DNEL, long-term		dermal	systemic	7,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	0,4 mg/m³
Consumer DNEL, long-term		dermal	local	2,66 mg/person/day
Consumer DNEL, long-term		oral	systemic	3,3 mg/kg bw/day
68608-26-4	Sulfonic acids, petroleum, sodium salts			
Worker DNEL, long-term		inhalation	systemic	0,66 mg/m³
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,33 mg/m³
Consumer DNEL, long-term		dermal	systemic	1667 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day
111-42-2	2,2'-iminodiethanol; diethanolamine			
Worker DNEL, long-term		inhalation	systemic	0,75 mg/m³
Consumer DNEL, long-term		inhalation	systemic	0,125 mg/m³
Worker DNEL, long-term		inhalation	local	0,5 mg/m³
Consumer DNEL, long-term		inhalation	local	0,125 mg/m³
Worker DNEL, long-term		dermal	systemic	0,130 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,07 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,06 mg/kg bw/day

2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			
Worker DNEL, long-term		inhalation	systemic	6,81 mg/m³
Worker DNEL, long-term		dermal	systemic	0,966 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,2 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,345 mg/kg bw/day
1310-73-2	Sodium hydroxide; caustic soda			
Worker DNEL, long-term		inhalation	local	1 mg/m³
Consumer DNEL, long-term		inhalation	local	1 mg/m³
1310-73-2	Sodium hydroxide; caustic soda			
Worker DNEL, long-term		inhalation	local	1 mg/m³
Consumer DNEL, long-term		inhalation	local	1 mg/m³

PNEC values

CAS No	Substance	
Environmental compartment		Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
105-59-9	2,2'-(methylimino)diethanol; N-methyldiethanolamine	
Freshwater		0,1 mg/l
Marine water		0,004 mg/l
Freshwater sediment		0,78 mg/kg
Marine sediment		0,035 mg/kg
Microorganisms in sewage treatment plants (STP)		10 mg/l
Soil		0,097 mg/kg
102-71-6	Triethanolamin	
Freshwater		0,32 mg/l
Marine water		0,32 mg/l
Freshwater sediment		1,7 mg/kg
Marine sediment		0,17 mg/kg
Microorganisms in sewage treatment plants (STP)		10 mg/l
Soil		0,151 mg/kg
68608-26-4	Sulfonic acids, petroleum, sodium salts	
Freshwater		1 mg/l
Marine water		1 mg/l
Freshwater sediment		723500000 mg/kg
Marine sediment		723500000 mg/kg
Secondary poisoning		16667 mg/kg
Microorganisms in sewage treatment plants (STP)		100 mg/l
Soil		868700000 mg/kg
111-42-2	2,2'-iminodiethanol; diethanolamine	
Freshwater		0,021 mg/l
Marine water		0,002 mg/l
Freshwater sediment		0,092 mg/kg
Marine sediment		0,0092 mg/kg
Soil		1,63 mg/kg
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	
Freshwater		4,03
Marine water (intermittent releases)		0,403
Freshwater sediment		49,9
Marine sediment		4,99
Microorganisms in sewage treatment plants (STP)		1,03 mg/l
Soil		3 mg/kg

8.2. Exposure controls






Individual protection measures, such as personal protective equipment

Eye/face protection

EN 166

Hand protection

Protect skin by using skin protective cream.
Wash hands before breaks and after work.
Gloves of appropriate material (i.e. nitrilic rubber, specification: penetration time: level 6, >480 min., thickness 0,9-1 mm; CE-certified acc. EN 374 cat III)

Skin protection

Chemical resistant safety shoes.
Take off immediately all contaminated clothing.
Thorough skin-cleansing after handling the product.
Set out skin protection guidelines.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Thermal hazards

Remove all sources of ignition.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	amber coloured
Odour:	characteristic

		Test method
Boiling point or initial boiling point and boiling range:	not determined	
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	not determined	DIN 51755
Auto-ignition temperature:	not determined	
pH-Value (at 20 °C):	10,9 (5% 9,5)	DIN 51369
Viscosity / kinematic: (at 20 °C)	94 mm²/s	ASTM D 7042
Vapour pressure:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	1,01 g/cm³	EN ISO 12185

9.2. Other information

Other safety characteristics

Pour point:	not determined
Viscosity / dynamic:	not determined

Further Information

in aqueous solution 5% pH 9,5

SECTION 10: Stability and reactivity

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.4. Conditions to avoid

Protect against: heat.

10.5. Incompatible materials

The following must be prevented: Oxidizing agents, strong. acid.

10.6. Hazardous decomposition products

Hazardous decomposition products: none

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalativ Dampf) > 20 mg/l; ATE (inhalativ Staub/Nebel) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified				
	oral	LD50 5000 mg/kg	Rat	ECHA	OECD Guideline 420
105-59-9	2,2'-(methylimino)diethanol; N-methyldiethanolamine				
	oral	LD50 4680 mg/kg	Rat		OECD 401
	dermal	LD50 > 2000 mg/kg	Rabit		
68608-26-4	Sulfonic acids, petroleum, sodium salts				
	oral	LD50 > 5001 mg/kg	Rat	Echa	OECD Guideline 401
	dermal	LD50 > 5001 mg/kg	Rat	Echa	OECD Guideline 402
4299-07-4	2-n-butyl-benzo[d]isothiazol-3-one				
	oral	LD50 4267-4732 mg/kg	Rat		
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one				
	oral	ATE 450 mg/kg			
	inhalation dust/mist	ATE 0,21 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.
Contains 2-n-butyl-benzo[d]isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

No risks worthy of mention. Practical experience.
The statement is derived from the properties of the single components.
The classification was undertaken in accordance with the calculation method governed by the Preparations Directive (1999/45/EC).

11.2. Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.
No information available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] | [d]	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified						
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Dickkopfelritze		
	Acute algae toxicity	ErC50 mg/l	> 100		Grünalgen		
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna		
	Crustacea toxicity	NOEC mg/l	10,0	21 d	Daphnia magna		
105-59-9	2,2'-(methylimino)diethanol; N-methyldiethanolamine						
	Acute fish toxicity	LC50 mg/l	1466	96 h	Leuciscus idus		DIN38412
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella sub.		DIN 38412
	Acute crustacea toxicity	EC50	233 mg/l	48 h	Daphnia magna		EU C.2
	Algae toxicity	NOEC mg/l	6,25	3 d	Desmodesmus subspicatus		DIN 38412
68608-26-4	Sulfonic acids, petroleum, sodium salts						
	Acute fish toxicity	LC50 mg/l	> 10000	96 h	marine species		
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	freshwater algae		
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna		
4299-07-4	2-n-butyl-benzo[d]isothiazol-3-one						
	Acute fish toxicity	LC50 mg/l	0,15	96 h	Oncorhynchus mykiss		OECD 203

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			
	OECD TG 301 B	30%	28	
	Inhärenter Schlamm	30 %	28	
105-59-9	2,2'-(methylimino)diethanol; N-methyldiethanolamine			
	OECD guideline 301 A	96%	18	
	readily biodegradable			
	OECD 302B	95%	14	
	inherently biodegradable			
	OECD 306	15%	63	
	not readily biodegradable			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
105-59-9	2,2'-(methylimino)diethanol; N-methyldiethanolamine	-1,16
68608-26-4	Sulfonic acids, petroleum, sodium salts	22,12
4299-07-4	2-n-butyl-benzo[d]isothiazol-3-one	<= 4,0

BCF

CAS No	Chemical name	BCF	Species	Source
105-59-9	2,2'-(methylimino)diethanol; N-methyldiethanolamine	0,7-3,2		

12.4. Mobility in soil

in delivery condition: liquid

12.5. Results of PBT and vPvB assessment

Based on available data, the classification criteria are not met.
none according to Regulation (EC) No. 1907/2006 (REACH)

12.6. Endocrine disrupting properties

Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

The waste key according to the European Waste Catalogue (EWC number) refers to the real wastes origin and therefore is not product- but use-oriented.

List of Wastes Code - residues/unused products

120107 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

List of Wastes Code - used product

120109 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; machining emulsions and solutions free of halogens; hazardous waste

List of Wastes Code - contaminated packaging

120109 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; machining emulsions and solutions free of halogens; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	No dangerous good in sense of these transport regulations.
14.2. UN proper shipping name:	No dangerous good in sense of these transport regulations.
14.3. Transport hazard class(es):	No dangerous good in sense of these transport regulations.
14.4. Packing group:	No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of these transport regulations.
14.2. UN proper shipping name:	No dangerous good in sense of these transport regulations.
14.3. Transport hazard class(es):	No dangerous good in sense of these transport regulations.
14.4. Packing group:	No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of these transport regulations.
14.2. UN proper shipping name:	No dangerous good in sense of these transport regulations.
14.3. Transport hazard class(es):	No dangerous good in sense of these transport regulations.
14.4. Packing group:	-

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of these transport regulations.
14.2. UN proper shipping name:	No dangerous good in sense of these transport regulations.
14.3. Transport hazard class(es):	No dangerous good in sense of these transport regulations.
14.4. Packing group:	-

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Personal protection equipment: see section 8

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,13,15.
AICS (Australien), DSL (Kanada), IECSC (China), REACH (Europäische Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (Neuseeland), PICCS (Philippinen), TSCA (USA)

Abbreviations and acronyms

Acute Tox. 2: Acute toxicity, hazard category 2
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Corr. 1B: Skin corrosion, sub-category 1B
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1: Skin sensitisation, hazard category 1
Skin Sens. 1A: Skin sensitisation, hazard category 1A
Carc. 2: Carcinogenicity, hazard category 2
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
Repr. - Reproduktionstoxizität
Asp. Tox. - Aspirationstoxizität
Acute Tox. - Akute Toxizität
Aquatic Acute - Akute aquatische Toxizität
Aquatic Chronic - Chronische aquatische Toxizität
Eye Dam. - Augenschaden/-reizung
Eye Irrit. - Augenreizung
Skin Corr. - Ätzwirkung auf die Haut
Skin Irrit. - Hautreizung
Skin Sens. - Hautallergen
Resp. Sens. - Inhalationsallergen
STOT SE - Spezifische Zielorgan-Toxizität - einmalige Exposition
STOT RE - Spezifische Zielorgan-Toxizität - wiederholte Exposition
VOC - Flüchtige organische Verbindungen
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
IMDG: International Maritime Code for Dangerous Goods
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
IATA: International Air Transport Association

ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
Abkürzungen und Akronyme siehe Verzeichnis unter http://abk.esdscom.eu

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH208	Contains 2-n-butyl-benzo[d]isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.
Abkürzungen und Akronyme siehe Verzeichnis unter http://abk.esdscom.eu

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)