

TECHNICAL DATA SHEET

JOKISCH KORIA NEFO 12.06 (Jokisch Corrosion Protection Oil DW Plus)

Builds a thin, vaseline like, self-healing protective film. Ensures an excellent water displacing and coating (wetting) effect, protects from fingerprints.

APPLICATION

Corrosion protection oil for metallic surfaces which need to be protected during storage. The product can be applied either by dipping, brushing or spraying. Protects metal parts from corrosive influences such as humidity, air or other contaminants.

CHARACTERISTICS

- Based on hydrocarbons, anti-corrosive and water-displacing additives
- Self-healing protective film
- Water displacing and coating (wetting) effect
- Protects from fingerprints

CORROSION PROTECTION TIME

Indoor storage: 12 months

Outdoor storage: 6 months

TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH KORIA NEFO 12.06
Kin. viscosity at 40°C	mm ² /s	ASTM D445	3,0
Density at 20°C	g/cm ³	DIN 51 757	0,81
Flash point	°C	ASTM D93	>62
Thickness	µm	-	2,7

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this.

STORAGE

Storage temperature: 5 – 40°C

Storage time: 36 months

Jokisch GmbH
Fabrik für Schmier- und Kühlmittelspezialitäten

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokisch-fluids.de | www.jokisch-fluids.de

