TECHNICAL DATA SHEET

JOKISCH FOTIA ALEA 1.W

Environmentally friendly, silicone free anti spatter fluid for MIG and MAG welding - suitable for X-ray welds.

Not-flammable – silicone free - chlorinated hydrocarbon free

APPLICATION

Active welding substance concentrate can be used for most common industrial welding process. Prevents the adherence of welding spatter to the workpiece surface.
Can be applied with hand sprayers or air spray cans.
Spray the work surface slightly, apply only thin spray film.

CHARACTERISTICS

- For arc welding with electrodes, easy removal of the slag, even with V-seams
- Easy cleaning of welding seams
- Also prevents the welding spatter from burning in the burner heads during inert gas welding and contact welding
- When used correctly no complications with further processing of priming, painting, galvanizing etc
- Product contains no water and therefor can be used for X-ray welds
- Product is exempted from the specific labelling requirements of hazardous products according to ordinance on hazardous substances

STORAGE

Storage temperature:	5 – 40°C
Storage time:	12 months

Date: 03.04.2025

JOKOBA Technologies GmbH

Industriestraße 5-10 | 33813 Oerlinghausen
T +49 52 02 97 34 0 | F +49 52 02 97 34 49
info@jokoba.de | www.jokisch-fluids.de

jokisch® Made in Germany